

# Aluminium Flexible



## 0.6/1kV Single Core

### XLPE Insulated, Rubber Sheathed Cable

Description: 0.6/1kV AL/X-HF-110/R ASNZS5000.1



**Application:** This cable can be used for mains power supply in switchboards and power stations. It can be installed in trenches, cable duct and cable trunking.

**Voltage Rating:** 0.6/1kV

**Construction:** Fine EC1350 Aluminium Wire, Class 5 ASNZS1125

**Insulation:** X-HF-110, White ASNZS3808

**Outer Sheath:** HF-110-Rubber, Black ASNZS3808, HFS (Halogen Free or LSZH)

**Temperature Range:** Min -25° , Max 110° , Flame Retardant

**Bending Radius:** 10 x OD

**Safe Pulling Force:** 9.37 MPa

Part Number	No of cores and nominal cross section area [mm]	Nominal Thickness of XLPE insulation [mm]	Thickness Of PVC Outer sheath	Overall diameter App.	Maximum wire OD	Diameter of Conductor	Net weight	D. C. resistance of conductor 20° (Ω/km)
	No*Section	Phase core	[mm]	[mm]	[mm]	[mm]	[kg/m]	Voltage withstand test(kV)-3.5
170ALFLEXRB	1*70	1.1	1.4	16.9	0.31	11.7	0.382	0.4430
195ALFLERXB	1*95	1.1	1.5	18.9	0.31	13.5	0.484	0.3200
1120ALFLEXRB	1*120	1.2	1.5	21.1	0.31	15.5	0.589	0.2530
1150ALFLEXRB	1*150	1.4	1.6	23.4	0.31	17.2	0.728	0.2060
1185ALFLEXRB	1*185	1.6	1.6	25.7	0.51	19.1	0.877	0.1640
1240ALFLEXRB	1*240	1.7	1.7	28.9	0.51	21.9	1.115	0.1250
1300ALFLEXRB	1*300	1.8	1.8	31.9	0.51	24.5	1.360	0.1000
1400ALFLEXRB	1*400	2.0	1.9	36.1	0.51	28.1	1.749	0.7780
1500ALFLEXRB	1*500	2.2	2.0	40.2	0.51	31.6	2.164	0.0605
1630ALFLEXRB	1*630	2.4	2.2	45.1	0.51	35.7	2.726	0.0469

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of ICSLTD is indicative only and shall not be binding on ICSLTD or be treated as constituting a representation on the part of ICSLTD.