

Flexible Fire Rated



0.6/1kV Single Core

XLPE Insulated, PVC Sheathed Cable

Description: 0.6/1kV CU/MICA/X-HF-110/HFS-110-TP



Application: This cable can be used for mains power supply in switchboards and power stations for essential circuits in a wiring system. It can withstand extreme temperature for 2 hours.

Voltage Rating: 0.6/1kV

Construction: Plain Annealed Copper, Circular

Stranded. Class 5, ASNZS1125

Insulation: X-HF-110 ASNZS3808

Standards: ASNZS3013 – WS52
AS/NZS 1660.5.1 / IEC 60332-3-22
AS/NZS 1660.5.2 / IEC 61034-2
AS/NZS 1660.5.3 / IEC 60754-1
AS/NZS 1660.5.4 / IEC 60754-2
AS/NZS 1660.5.5 / IEC 60331

Bending Radius: 12 x OD

Part Number	No of cores and nominal cross section area [mm]	Nominal Thickness of insulation [mm]	Thickness of Outer sheath	Overall diameter App.	Maximum wire OD	Diameter of Conductor	Net weight	D. C. resistance of conductor 20°C (Ω/km)
	No*Section	Phase core	[mm]	[mm]	[mm]	[mm]	[kg/m]	Voltage withstand test(kV)-3.5
116CUFLEXFR	1*16	0.7	1.4	11.9	0.41	5.5	0.279	1.210
125CUFLEXFR	1*25	0.9	1.4	13.8	0.41	7.0	0.343	0.780
135CUFLEXFR	1*35	0.9	1.4	15.2	0.41	8.4	0.444	0.554
150CUFLEXFR	1*50	1.0	1.4	16.9	0.41	9.9	0.54	0.386
170CUFLEXFR	1*70	1.1	1.4	18.7	0.51	11.5	0.757	0.272
195CUFLEXFR	1*95	1.1	1.5	20.6	0.51	13.2	1.025	0.206
1120CUFLEXFR	1*120	1.2	1.5	22.6	0.51	15.0	1.274	0.161
1150CUFLEXFR	1*150	1.4	1.6	25.0	0.51	16.8	1.854	0.129
1185CUFLEXFR	1*185	1.6	1.6	27.5	0.51	18.7	1.94	0.106
1240CUFLEXFR	1*240	1.7	1.7	30.5	0.51	21.3	2.00	0.0801
1300CUFLEXFR	1*300	1.8	1.8	33.6	0.51	24.0	3.145	0.0641
1400CUFLEXFR	1*400	2.0	1.9	38.0	0.51	27.8	4.003	0.0486
1500CUFLEXFR	1*500	2.2	2	41.4	0.61	30.6	5.105	0.0384
1630CUFLEXFR	1*630	2.4	2.2	45.6	0.61	34.0	6.462	0.0287

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of ICSLTD is indicative only and shall not be binding on ICSLTD or be treated as constituting a representation on the part of ICSLTD.

Flexible Fire Rated



Description: 0.6/1kV CU/MICA/X-HF-110/HFS-110-TP

Current-Carrying Capacity

Two Single Core

Reference Ambient Temperature: 30°C in air and 15°C in ground

Conductor Size	Unenclosed Spaced	Unenclosed Spaced from surface	Unenclosed Touching	Enclosed Touching	Buried Direct	Underground wiring enclosure	Underground wiring enclosure
[mm]							
10	109	105	86	82	93	91	103
16	144	138	112	109	163	119	135
25	190	182	149	142	210	152	173
35	236	225	184	179	252	187	207
50	299	281	233	221	299	228	250
70	376	352	292	281	367	282	305
95	452	423	352	334	441	331	373
120	535	499	417	389	501	381	424
150	617	574	482	456	563	439	475
185	706	654	552	515	637	492	548
240	850	783	664	624	740	581	636
300	980	900	766	.	836	669	736
400	1182	1076	920	.	952	778	837
500	1380	1245	1069	.	1079	906	976
630	1636	1454	1250	.	1217	1036	1108

Note: Please be advised that the information contained in this table, along with the typical installation conditions applicable in New Zealand, is sourced from AS/NZS 3008.1.2:2017. This content has been utilised with the express permission of Standards New Zealand under Copyright Licence SZ00025278 and has either been reproduced or adapted. For comprehensive details, we recommend consulting the entire Standard, which can be obtained for purchase directly from Standards New Zealand via www.standards.co.nz.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of ICSLTD is indicative only and shall not be binding on ICSLTD or be treated as constituting a representation on the part of ICSLTD.