

PVC - Insulated Cables



0.6/1kV Single Core PVC Sheathed Cable

Description: 0.6/1kV CU/PVC ASNZS5001.1



Application: This cable can be used for mains power supply in switchboards and power stations. It can be installed in trenches, cable duct and cable trunking.

Voltage Rating: 0.6/1kV

Construction: Plain Annealed Copper, Circular Non-Compacted stranded, Class 2, ASNZS1125, Tinned copper option available.

Outer Sheath: Extruded Polyvinyl Chloride Compound (PVC/SV-90), Colour – Green Yellow

Sheath Option: HFS (Halogen Free) – LSZH

Bending Radius: 9 x OD

Part Number	No of cores and nominal cross section area [mm]	Thickness Of PVC Outer sheath	Overall diameter App.	Stranding	Maximum wire OD	Diameter of Conductor	Net weight	D. C. resistance of conductor 20°C (Ω/km)
	No*Section	[mm]	[mm]	[Wires]	[mm]	[mm]	[kg/m]	Voltage withstand test(kV)-3.5
4GY	1*4	1.0	4.8	7/0.85	0.85	2.55	0.054	4.610
6GY	1*6	1.0	5.3	7/1.04	1.04	3.12	0.074	3.080
10GY	1*10	1.0	6.3	7/1.35	1.35	4.05	0.115	1.830
16GY	1*16	1.0	7.3	7/1.70	1.70	5.10	0.173	1.150
25GY	1*25	1.2	9.0	7/2.12	2.12	6.36	0.266	0.727
35GY	1*35	1.2	10.2	7/2.52	2.52	7.56	0.365	0.524
50GY	1*50	1.4	11.9	19/1.78	1.78	8.90	0.494	0.387
70GY	1*70	1.4	13.7	19/2.14	2.14	10.70	0.695	0.268
95GY	1*95	1.6	16.0	19/2.52	1.78	12.60	0.933	0.193
120GY	1*120	1.6	17.6	37/2.03	2.03	14.21	1.195	0.153
150GY	1*150	1.8	19.6	37/2.25	2.25	15.75	1.469	0.124
185GY	1*185	2.0	21.8	37/2.52	2.52	17.64	1.840	0.099
240GY	1*240	2.2	24.9	61/2.25	2.25	20.25	2.407	0.075
300GY	1*300	2.4	27.7	61/2.52	2.52	22.68	3.010	0.060
400GY	1*400	2.6	31.1	61/2.85	2.85	25.65	3.832	0.047

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of ICSLTD is indicative only and shall not be binding on ICSLTD or be treated as constituting a representation on the part of ICSLTD.